

	<p data-bbox="948 282 1350 353">Xi'- An LIB environmental simulation industry</p>  <p data-bbox="991 571 1307 600"><i>South America distributor:</i></p> <p data-bbox="868 622 1433 674"><i>www.GtemCell.com</i></p> <p data-bbox="1118 674 1190 689">ITALIA</p>
---	---

Walk-in rooms

Purpose and features of the product: This product series are in piece assembling structure, which enables on-site installation and commissioning. They are equipped with separate controlling chamber or operation bench. With large volume, the work chamber can be used to simulate the single or complicated environmental factors in the atmosphere such as temperature, humidity, salt fog, illumination, wind, rain and vibration. The products can be used to analyze and evaluate the property and performance of the batch elements and parts or machine sets under simulated conditions, and can also be used in experiment and production.

Product name	Type	Dimensions of work chamber (cm)	Volume (m3)	Temperature range (°C)	Implementation/satisfaction standard
	HTT1003F	150×120×150	3	R.T.+10°C~+100°C	GB11158-89 GB2423.2-89 GB2423.2-89
	HTT1005F	200×120×200	5		
	HTT1008F	200×200×200	8		
	HTT1010F	250×200×200	10		
	HTT1015F	380×200×200	15		
	HTT1020F	400×250×200	20		
	HTT1025F	400×250×250	25		
	HTT1030F	400×300×250	30		
	HTT1050F	500×400×250	50		
	HTT1080F	800×400×250	80		
HTT1100F	1000×400×250	100			

Temperature & humidity walking room

Product name	Type	Dimensions of work chamber (cm)	Volume (m3)	Temperature range (°C)	Note	satisfaction standard
Temperature & humidity test chamber test room	HRT6003F	150×120×150	3	HRTR-F Series R.T.+10°C~+85°C, HRT0-F Series :-5°C~+85°C, HRT2-F Series: -20°C~+85°C, HRT4-F Series: -40°C~+85°C,	HRTR-F Series Humidity range: 60~95%R.H., other humidity range:30~95%R.H.	GB10586, GB10589, GB/T2423.3, IEC68-2-3, IEC68-2-1, IEC68-2-30, GB/T2423.4
	HRT6005F	200×120×200	5			
	HRT4008F	200×200×200	8			
	HRT4010F	250×200×200	10			
	HRT2015F	380×200×200	15			
	HRT2020F	400×200×250	20			
	HRT0030F	400×300×250	30			
	HRT0050F	500×400×250	50			
	HRTR080F	800×400×250	80			
	HRTR100F	1000×400×250	100			

Product name	Type	Dimensions of work chamber (cm)	Volume (m3)	Temperature range (°C)	satisfaction standard
High-low temperature test room	HLT0003F	150×120×150	3	HLT0-F Series -5°C~+85°C, HLT2-F Series -20°C~+85°C, HLT4-F Series -40°C~+85°C, HLT6-F Series -65°C~+85°C	GB10592-89 GB2423.1-89-A HEC68-2-1-A GB2423.22-89-Nb GJB150.3-86
	HLT0005F	200×120×200	5		
	HLT0008F	200×200×200	8		
	HLT2010F	250×200×200	10		
	HLT2015F	380×200×200	15		
	HLT2020F	400×200×250	20		
	HLT4030F	400×300×250	30		
	HLT4050F	500×400×250	50		
	HLT6080F	800×400×250	80		
	HLT6100F	1000×400×250	100		

High and low temperature walking room

Product name	Type	Dimensions of work chamber (cm)	Volume (m3)	Temperature range (°C)	satisfaction standard
High-low temperature test room	HLT0003F	150×120×150	3	HLT0-F Series -5°C~+85°C, HLT2-F Series -20°C~+85°C, HLT4-F Series -40°C~+85°C, HLT6-F Series -65°C~+85°C	GB10592-89 GB2423.1-89-A HEC68-2-1-A GB2423.22-89-Nb GJB150.3-86
	HLT0005F	200×120×200	5		
	HLT0008F	200×200×200	8		
	HLT2010F	250×200×200	10		
	HLT2015F	380×200×200	15		
	HLT2020F	400×200×250	20		
	HLT4030F	400×300×250	30		
	HLT4050F	500×400×250	50		
	HLT6080F	800×400×250	80		
	HLT6100F	1000×400×250	100		

■ **Structure characteristics**

1. Equipment structure takes up stainless steel plate plus (41090) power for hull painting. It not only has good profile, but also has fine corrosion resistance.
2. It utilizes imported closed-type compressor unit imported from Europe and USA, which has solid and durable structure and is durable and can greatly enhance service property and life of the equipment; it takes up advanced energy-saving design, which can save electric power by 30%, save water by 20%, and it uses HFC refrigerant that will not harm human body and nature, you can conduct test in safe way;
3. It has advanced and innovative control theory, it integrates three control systems of PLC, HMI and SOC in fine way. Control is correct by 100%, and you can experience the novel control feeling;
4. It utilizes most powerful and reliable PLC and special modules in the industry circle. 50 programs and 2500 steps are provided for user to make setting/storage and running;
5. It utilizes protection module for safe voltage, the withstand voltage can reach 500V. After energizing the equipment, the equipment will not be burned and it can protect the equipment by 100%.
6. It takes up high-sense FastAIT monitoring and refrigerating system imported and achieves effective control and management for refrigerant volume;
8. It has automatic safety protection switch, which has high sensitivity, can detect any state, cut off protection and give alarm in shortest time and assure safety of the personnel and equipment;
7. It utilizes the advanced USB storage device in the industry. It is the only one for using the USB interface for storing data. It has not only large storage capacity and fast transmission rate, but also is portable, has great supporting property and is convenient.;
8. It can separately raise temperature, reduce temperature, humidify and dehumidify, it utilizes unique BTHC flat constant temperature and humidity regulating mode;
9. The radio tele-monitoring system takes up IPC/SCADA architecture LAN network interface, it can connect to more than 200 equipments at the same time, and it can avoid the complex wiring and eliminate the regional limit;
10. Large temperature and humidity range: 20~98%RH, the moisture can reach within 10%RH after installing the dehumidifying device;
11. It has air supply and circulating system, which can avoid dead angle of air flow in the chamber and improve the uniformity degree of product temperature and humidity.

■ **Control system:**

TEMI880 touch-key type temperature and humidity programmable controller

Operating interface: LED display

Temperature and humidity controller: touch-type LED controller

Setting mode: touching type

Running mode: setting-up running and programmed running

Program: 100 groups in 1000 sections

Resolution: temperature: ± 0.1 °C; humidity: $\pm 1\%$ RH

Input: platinum thermal resistance

Control mode: PID control

Communication function: LAN network interface

Additional function: alarm and display function, power-off protection function, upper limit temperature alarm function, timing function (auto startup and auto stop), self-diagnosis function, curve record and display function, paperless record, USB data export, tele-monitoring and so on.

It can execute 100 STEP X 10 PATTEM mode.

Each section can be grouped and executed in crossing way.

The execution time for each section can be set up between 0-999H plus 59min.

For setting up for each group, it can circulate within 1-999 in part or entirely for option.

In execution, it can select group circle picture or section execution picture and can know the remaining time for execution.

It has power-off function. After power recovery, it can complete the remained test.

It can select single-section control or multi-section programmable control.

The screen has backlight time control function and it can adjust the backlight brightness.

For executing single-section control, it can change the execution value at will. The memory-type multi-function control has automatic control output functions, such as heating heater and humidifying heater for electromechanical solenoid valve for different groups of refrigerating compressors and so on.

■ **Water supply**

Water supply mode: water lifted by pump

Water supply port: convenient front water supply port

Water storage tank: built-in stainless steel fixed-type water storage tank (with a volume about 15L)

■ **Safety device**

Humidifier dry-combustion protection, independent over-temperature protection, water shortage protection, over-current protection, refrigerant high-pressure protection switch, over-current circuit breaker, earth leakage protection and so on.

■ **Operation ambient temperature:** +5°C~ + 30°C

■ **Power supply :** AC380 \pm 10%V 50 \pm 0.5Hz single-phase double-wire + protective grounding wire/
AC380 \pm 10%V 50 \pm 0.5Hz three-phase four-wire+ protective grounding wire

■ **Accessory**

1 cable hole (Φ 50,) cover, 2 sets of shelf, 2 protector tubes, 1 overflow water tube, 1 copy of operating specification

■ **Optional accessory:**

recorder, tele-monitoring software

Note:

1. The products above can be customized according to demands of the clients;
2. The technical parameters above are the data obtained under room temperature of 20°C and non-load condition.

Implementation and meet the standards

1. GB/T10586-1989 damp heat test chambers;
2. GB/T10589-1989 temperature test chambers;
3. GB/T10592-1989 high-temperature test chambers;
4. GB/T2423.423.3-93 (IEC 68-2-3) Damp heat test Ca;

